

Hockey G7.0.0 300lx 150812c

Hockey Field

Field dimensions: 91.4m x 55m

Mounting height: 15m

Number of poles: 8

Number of fixtures: 12

Lighting class: EN-12193 class II

Horizontal illuminance in use = 300 lux

Uniformity E_{hmin}/E_{hgem} = 0.7

AAA-LUX LED luminaire used: 8x WS2707 and 4x WS2907

IES files vRC 7.0.0 - date: 15 Jun 2020

The nominal values shown in this report are the result of precision calculations, based upon precisely positioned luminaires in a fixed relationship to each other and to the area under examination. In practice the values may vary due to tolerances on luminaires, luminaire positioning, reflection properties and/or electrical supply. Tolerated differences are defined in EN-12193 clause 5.4 with a maximum of 10%.

Date: 22.06.2020

Operator: PM

AAA-LUX
Eindhoven
The Netherlands
www.aaa-lux-lighting.com

Operator PM
Telephone
Fax
e-Mail

Table of contents

Hockey G7.0.0 300lx 150812c	
Project Cover	1
Table of contents	2
AAA-LUX WS2907vRC 7.0.0	
Luminaire Data Sheet	3
AAA-LUX WS2707vRC 7.0.0	
Luminaire Data Sheet	4
Hockey	
Sport Luminaires (Coordinates List)	5
Exterior Surfaces	
Calculation Grid according EN12193	
Value Chart (E, Horizontal)	7


AAA-LUX
Eindhoven
The Netherlands
www.aaa-lux-lighting.com

Operator PM
Telephone
Fax
e-Mail

AAA-LUX WS2907vRC 7.0.0 / Luminaire Data Sheet

Luminous emittance 1:

See our luminaire catalog for an image of the luminaire.



Luminaire classification according to CIE: 99
CIE flux code: 72 91 98 99 86

Due to missing symmetry properties, no UGR table
can be displayed for this luminaire.


AAA-LUX
Eindhoven
The Netherlands
www.aaa-lux-lighting.com

Operator PM
Telephone
Fax
e-Mail

AAA-LUX WS2707vRC 7.0.0 / Luminaire Data Sheet

Luminous emittance 1:

See our luminaire catalog for an image of the luminaire.




Luminaire classification according to CIE: 100
CIE flux code: 91 97 99 100 85

Due to missing symmetry properties, no UGR table
can be displayed for this luminaire.

AAA-LUX
 Eindhoven
 The Netherlands
www.aaa-lux-lighting.com

Operator PM
 Telephone
 Fax
 e-Mail

Hockey / Sport Luminaires (Coordinates List)



Scale 1 : 1000

List of the Sport Luminaires

Luminaire	Index	Position [m]			Aiming Point [m]			Angle [°]	Alignment	Pole
		X	Y	Z	X	Y	Z			
AAA-LUX WS2707vRC 7.0.0	1	-50.000	-29.500	15.200	-21.300	-19.000	0.000	26.4	(C 0, G 0)	/
AAA-LUX WS2707vRC 7.0.0	1	-50.000	-29.500	15.200	-38.100	-3.900	0.000	28.3	(C 0, G 0)	/
AAA-LUX WS2707vRC 7.0.0	2	50.000	-29.500	15.200	21.300	-19.000	0.000	26.4	(C 0, G 0)	/
AAA-LUX WS2707vRC 7.0.0	2	50.000	-29.500	15.200	38.100	-3.900	0.000	28.3	(C 0, G 0)	/

AAA-LUX
 Eindhoven
 The Netherlands
www.aaa-lux-lighting.com

Operator PM
 Telephone
 Fax
 e-Mail

Hockey / Sport Luminares (Coordinates List)


List of the Sport Luminares

Luminaire	Index	Position [m]			Aiming Point [m]			Angle [°]	Alignment	Pole
		X	Y	Z	X	Y	Z			
AAA-LUX WS2707vRC 7.0.0	3	-50.000	29.500	15.200	-21.300	19.000	0.000	26.4	(C 0, G 0)	/
AAA-LUX WS2707vRC 7.0.0	3	-50.000	29.500	15.200	-38.100	3.900	0.000	28.3	(C 0, G 0)	/
AAA-LUX WS2707vRC 7.0.0	4	50.000	29.500	15.200	21.300	19.000	0.000	26.4	(C 0, G 0)	/
AAA-LUX WS2707vRC 7.0.0	4	50.000	29.500	15.200	38.100	3.900	0.000	28.3	(C 0, G 0)	/
AAA-LUX WS2907vRC 7.0.0	5	-16.000	-29.500	15.200	-7.800	-6.900	0.000	32.3	(C 0, G 0)	/
AAA-LUX WS2907vRC 7.0.0	6	16.000	-29.500	15.200	7.800	-6.900	0.000	32.3	(C 0, G 0)	/
AAA-LUX WS2907vRC 7.0.0	7	-16.000	29.500	15.200	-7.800	6.900	0.000	32.3	(C 0, G 0)	/
AAA-LUX WS2907vRC 7.0.0	8	16.000	29.500	15.200	7.800	6.900	0.000	32.3	(C 0, G 0)	/

AAA-LUX
 Eindhoven
 The Netherlands
www.aaa-lux-lighting.com


Operator PM
 Telephone
 Fax
 e-Mail

Hockey / Calculation Grid according EN12193 / Value Chart (E, Horizontal)



Values in Lux, Scale 1 : 750

Position of surface in external scene:
 Marked point: (-45.000 m, -25.000 m,
 0.000 m)



Grid: 19 x 11 Points

E_{av} [lx]
 334

E_{min} [lx]
 259

E_{max} [lx]
 455

u_0
 0.77

E_{min} / E_{max}
 0.57