

Soccer G7.0.0 120lx 150606c

Soccer Field

Field dimensions: 100m x 64m

Mounting height: 15m

Number of poles: 6

Number of fixtures: 6

Lighting class: EN-12193 class III

Horizontal illuminance in use = 75 lux

Uniformity E_{hmin}/E_{hgem} = 0.5

AAA-LUX LED luminaire used: 4x WS2007 and 2x WS2907

IES files vRC 7.0.0 - date: 15 Jun 2020

The nominal values shown in this report are the result of precision calculations, based upon precisely positioned luminaires in a fixed relationship to each other and to the area under examination. In practice the values may vary due to tolerances on luminaires, luminaire positioning, reflection properties and/or electrical supply. Tolerated differences are defined in EN-12193 clause 5.4 with a maximum of 10%.

Date: 22.06.2020

Operator: MVD

AAA-LUX
Eindhoven, NL
www.aaa-lux-lighting.com
sales@aaa-lux-lighting.com

Operator MVD
Telephone
Fax
e-Mail

Table of contents

Soccer G7.0.0 120lx 150606c	
Project Cover	1
Table of contents	2
Soccer	
Luminaire parts list	3
Sport Luminaires (Coordinates List)	4
Exterior Surfaces	
Calculation grid according EN12193	
Value Chart (E, Horizontal)	6


AAA-LUX
Eindhoven, NL
www.aaa-lux-lighting.com
sales@aaa-lux-lighting.com

Operator MVD
Telephone
Fax
e-Mail

Soccer / Luminaire parts list


4 Pieces AAA-LUX WS2007vRC 7.0.0
Article No.:
Luminous flux (Luminaire): 188123 lm
Luminous flux (Lamps): 221072 lm
Luminaire Wattage: 1550.0 W
Luminaire classification according to CIE: 100
CIE flux code: 86 97 99 100 85
Fitting: 1 x LED SOURCE AAA-LUX (Correction Factor 1.000).

See our luminaire catalog for an image of the luminaire.



2 Pieces AAA-LUX WS2907vRC 7.0.0
Article No.:
Luminous flux (Luminaire): 189212 lm
Luminous flux (Lamps): 221072 lm
Luminaire Wattage: 1550.0 W
Luminaire classification according to CIE: 99
CIE flux code: 72 91 98 99 86
Fitting: 1 x LED SOURCE AAA-LUX (Correction Factor 1.000).


See our luminaire catalog for an image of the luminaire.



AAA-LUX
 Eindhoven, NL
 www.aaa-lux-lighting.com
 sales@aaa-lux-lighting.com

Operator MVD
 Telephone
 Fax
 e-Mail

Soccer / Sport Luminaires (Coordinates List)



Scale 1 : 1000

List of the Sport Luminaires

Luminaire	Index	Position [m]			Aiming Point [m]			Angle [°]	Alignment	Pole
		X	Y	Z	X	Y	Z			
AAA-LUX WS2007vRC 7.0.0	1	-52.500	-36.000	15.200	-30.500	-8.600	0.000	23.4	(C 0, G 0)	/
AAA-LUX WS2007vRC 7.0.0	2	52.500	-36.000	15.200	30.500	-8.600	0.000	23.4	(C 0, G 0)	/
AAA-LUX WS2007vRC 7.0.0	3	-52.500	36.000	15.200	-30.500	8.600	0.000	23.4	(C 0, G 0)	/
AAA-LUX WS2007vRC 7.0.0	4	52.500	36.000	15.200	30.500	8.600	0.000	23.4	(C 0, G 0)	/

AAA-LUX
 Eindhoven, NL
www.aaa-lux-lighting.com
sales@aaa-lux-lighting.com

Operator MVD
 Telephone
 Fax
 e-Mail

Soccer / Sport Luminaires (Coordinates List)

List of the Sport Luminaires

Luminaire	Index	Position [m]			Aiming Point [m]			Angle [°]	Alignment	Pole
		X	Y	Z	X	Y	Z			
AAA-LUX WS2907vRC 7.0.0	5	0.000	-36.000	15.200	0.100	-9.200	0.000	29.6	(C 0, G 0)	/
AAA-LUX WS2907vRC 7.0.0	6	0.000	36.000	15.200	0.100	9.200	0.000	29.6	(C 0, G 0)	/

AAA-LUX
Eindhoven, NL
www.aaa-lux-lighting.com
sales@aaa-lux-lighting.com

Operator MVD
Telephone
Fax
e-Mail

Soccer / Calculation grid according EN12193 / Value Chart (E, Horizontal)



Values in Lux, Scale 1 : 750

Position of surface in external scene:
Marked point: (-50.000 m, -32.000 m,
0.000 m)



Grid: 21 x 13 Points

E_{av} [lx]
135

E_{min} [lx]
97

E_{max} [lx]
186

u_0
0.72

E_{min} / E_{max}
0.52