

Soccer G7.0.0 200lx 150612

Soccer Field

Field dimensions: 100m x 64m

Mounting height: 15m

Number of poles: 6

Number of fixtures: 12

Lighting class: EN-12193 class II

Horizontal illuminance in use = 200 lux

Uniformity E_{hmin}/E_{hgem} = 0.6

AAA-LUX LED luminaire used: 12x WS2907

IES files vRC 7.0.0 - date: 15 Jun 2020

The nominal values shown in this report are the result of precision calculations, based upon precisely positioned luminaires in a fixed relationship to each other and to the area under examination. In practice the values may vary due to tolerances on luminaires, luminaire positioning, reflection properties and/or electrical supply. Tolerated differences are defined in EN-12193 clause 5.4 with a maximum of 10%.

Date: 22.06.2020

Operator: MVD

AAA-LUX
Eindhoven, NL
www.aaa-lux-lighting.com
sales@aaa-lux-lighting.com

Operator MVD
Telephone
Fax
e-Mail sales@aaa-lux-lighting.com

Table of contents

Soccer G7.0.0 200lx 150612

Project Cover	1
Table of contents	2
Soccer	
Luminaire parts list	3
Sport Luminaires (Coordinates List)	4
Exterior Surfaces	
Calculation grid according EN12193	
Value Chart (E, Horizontal)	6


AAA-LUX
Eindhoven, NL
www.aaa-lux-lighting.com
sales@aaa-lux-lighting.com

Operator MVD
Telephone
Fax
e-Mail sales@aaa-lux-lighting.com

Soccer / Luminaire parts list

12 Pieces AAA-LUX WS2907vRC 7.0.0
Article No.:
Luminous flux (Luminaire): 189212 lm
Luminous flux (Lamps): 221072 lm
Luminaire Wattage: 1550.0 W
Luminaire classification according to CIE: 99
CIE flux code: 72 91 98 99 86
Fitting: 1 x LED SOURCE AAA-LUX (Correction
Factor 1.000).


See our luminaire
catalog for an image of
the luminaire.



AAA-LUX
Eindhoven, NL
www.aaa-lux-lighting.com
sales@aaa-lux-lighting.com

Operator MVD
Telephone
Fax
e-Mail sales@aaa-lux-lighting.com

Soccer / Sport Luminares (Coordinates List)



Scale 1 : 750

List of the Sport Luminares

Luminaire	Index	Position [m]			Aiming Point [m]			Angle [°]	Alignment	Pole
		X	Y	Z	X	Y	Z			
AAA-LUX WS2907vRC 7.0.0	1	-33.500	-36.000	15.200	-33.600	-5.600	0.000	26.6	(C 0, G 0)	/
AAA-LUX WS2907vRC 7.0.0	1	-33.500	-36.000	15.200	-39.000	-7.800	0.000	27.9	(C 0, G 0)	/
AAA-LUX WS2907vRC 7.0.0	2	33.500	-36.000	15.200	33.600	-5.600	0.000	26.6	(C 0, G 0)	/
AAA-LUX WS2907vRC 7.0.0	2	33.500	-36.000	15.200	39.000	-7.800	0.000	27.9	(C 0, G 0)	/

AAA-LUX
 Eindhoven, NL
 www.aaa-lux-lighting.com
 sales@aaa-lux-lighting.com

Operator MVD
 Telephone
 Fax
 e-Mail sales@aaa-lux-lighting.com

Soccer / Sport Luminares (Coordinates List)


List of the Sport Luminares

Luminaire	Index	Position [m]			Aiming Point [m]			Angle [°]	Alignment	Pole
		X	Y	Z	X	Y	Z			
AAA-LUX WS2907vRC 7.0.0	3	-33.500	36.000	15.200	-33.600	5.600	0.000	26.6	(C 0, G 0)	/
AAA-LUX WS2907vRC 7.0.0	3	-33.500	36.000	15.200	-39.000	7.800	0.000	27.9	(C 0, G 0)	/
AAA-LUX WS2907vRC 7.0.0	4	33.500	36.000	15.200	33.600	5.600	0.000	26.6	(C 0, G 0)	/
AAA-LUX WS2907vRC 7.0.0	4	33.500	36.000	15.200	39.000	7.800	0.000	27.9	(C 0, G 0)	/
AAA-LUX WS2907vRC 7.0.0	5	0.000	-36.000	15.200	-5.000	-6.500	0.000	26.9	(C 0, G 0)	/
AAA-LUX WS2907vRC 7.0.0	5	0.000	-36.000	15.200	4.900	-6.400	0.000	26.9	(C 0, G 0)	/
AAA-LUX WS2907vRC 7.0.0	6	0.000	36.000	15.200	-5.000	6.500	0.000	26.9	(C 0, G 0)	/
AAA-LUX WS2907vRC 7.0.0	6	0.000	36.000	15.200	4.900	6.400	0.000	26.9	(C 0, G 0)	/

AAA-LUX
Eindhoven, NL
www.aaa-lux-lighting.com
sales@aaa-lux-lighting.com

Operator MVD
Telephone
Fax
e-Mail sales@aaa-lux-lighting.com

Soccer / Calculation grid according EN12193 / Value Chart (E, Horizontal)



Values in Lux, Scale 1 : 750

Position of surface in external scene:
Marked point: (-50.000 m, -32.000 m,
0.000 m)



Grid: 21 x 13 Points

E_{av} [lx]	E_{min} [lx]	E_{max} [lx]	u_0	E_{min} / E_{max}
255	185	332	0.73	0.56